

Modules + Processes

P. Marwedel*
Informatik 12, U. Dortmund


* Partially using slides prepared by Tatjana Stankovic from the University of Nis (Serbia and Montenegro), visiting the University of Dortmund under the TEMPUS program.
These slides contain Microsoft cliparts. All usage restrictions apply.

Contents

- Introduction
- Data types
- A Notion of Time
- ➔ ■ Modules
- Concurrency
- Structure
- Communication, Channels
- Ports & Interfaces
- Advanced Topics



SystemC language architecture



Modules

- Modules are basic building blocks of a SystemC design
- A module contains
 - processes (→ **functionality**)
 - and/or sub-modules (→ **hierarchical structure**)
- Modules can be
 - described with the **SC_MODULE** macro
 - or derived explicitly from **sc_module**

Modules

SC_MODULE is a macro shorthand for deriving module classes from the library class **sc_module**.

Syntax:

```
SC_MODULE (module_name) {  
    module_body  
};
```

Definition of SC_MODULE:

```
#define SC_MODULE (module_name) \  
    struct module_name: public sc_module
```

Elements of the module body

```
SC_MODULE( module_name ) {  
    // Declaration of module ports  
    // Member channel instances  
    // Member data instances  
    // Member module instances (sub-designs)  
    // Constructor  
    // Destructor  
    // Process member functions (processes)  
    // Helper functions  
};
```

The **SC_MODULE** Class Constructor: **SC_CTOR**

A module must contain a C++ constructor.
Constructors should be built using the SystemC macro **SC_CTOR** or include **SC_HAS_PROCESS** (*module_name*);

Syntax for **SC_CTOR**:

```
SC_CTOR(module_name)  
: Initialization // optional  
{ sub-design allocation  
  sub-design connectivity  
  process_registration  
  miscellaneous setup  
}
```

The constructor must

- Initialize/allocate sub-designs
- Connect sub-designs
- Declare event sensitivities
- Register processes with the SystemC kernel.

Contents

- Introduction
- Data types
- A Notion of Time
- Modules
- ➔ ■ Concurrency
- Structure
- Communication, Channels
- Ports & Interfaces
- Advanced Topics



Processes

Definition: A SystemC **process** is a member function or class method of an **SC_MODULE** that is invoked by the scheduler of the SystemC simulation kernel.

Syntax:

void *process_name*(**void**);

SC_THREAD

Threads are simple processes created with the **SC_THREAD** macro.

Syntax:

SC_THREAD(*process_name*);

Registration by using the macro within the constructor.

Context:

```
SC_MODULE(simple_process){  
    SC_CTOR(simple_process) {  
        SC_THREAD(thread_process);  
    }  
    void thread_process(void);  
};
```

SC_THREAD

Processes created using **SC_THREAD**

- are started once,
- execute until they call **wait()** or **return**, (**wait()** may be called indirectly via blocking read or write calls)
- frequently comprise infinite loops including **wait** calls,
- provide **persistence** for all local variables,
- roughly correspond to processes in an operating system using "cooperative multitasking" or coroutines.

SC_THREAD::wait()

Examples:

wait(*time*);

wait(*event*);


wait(*event* [, | *event*]); // any event causes resume

wait(*event* [, & *event*]); // all events req. for resume

wait(*timeout*, *event*); // event with timeout

wait(); // use static sensitivity

Function **time_out()** may be called immediately after a wait to check if **wait** was terminated by timeout.



SC_METHOD

Macro **SC_METHOD** can be used to create a process within a constructor. Such a process



- *Always runs to completion*;
- Cannot call **wait()** or blocking **read** and **write** methods.
- Is more efficient than processes created with **SC_THREAD**.
- Loses the values of all variables upon exit.

next_trigger()

The **next_trigger()** method can be used to specify the sensitivity of **SC_METHODs**. The last call of **next_trigger** preceding an exit from an **SC_METHODs** specifies the condition for re-entry.

Example:

next_trigger(*time*);

next_trigger(*event* [, | *event*]); // any event causes restart

next_trigger(*event* [, & *event*]); // all events req. for restart

next_trigger(*timeout*, *event*); // event with timeout

next_trigger(); // back to static sensitivity

Static sensitivity

Static sensitivity is an alternative to using **wait()** or **next_trigger()**. Static sensitivity is established at compile time.

Static sensitivity applies to the most recent process registration.

2 syntactical forms:

1. Streaming style:

sensitive << *event* [<<*event*] ...;

2. "Functional style"

sensitive (*event* [, *event*] ..);

don't_initialize

Normally, all processes are started initially.

This can be avoided by calling **dont_initialize()**.

The call must follow process registration.

A static sensitivity list should be used with **dont_initialize**, otherwise the process would never be executed.

Example:

...

```
SC_METHOD(attendant_method);  
    sensitive(fillup_request);  
    dont_initialize();
```

...

Contents


- Introduction
- Data types
- A Notion of Time
- Modules
- Concurrency
- ➔ ■ Structure
- Communication, Channels
- Ports & Interfaces
- Advanced Topics



Design Hierarchy



Example



Different module instantiation approaches:

- in the header or the implementation file,
- direct instantiation in declaration or dynamic creation with pointers,
- at top level of the hierarchy or at some other level.

Combinations thereof.

Direct Top-Level Instantiation

Example:

```
//file: main.cpp
#include "Wheel.h"
int sc_main (int argc, char* argv[] {
Wheel wheel_FL("wheel_FL");
Wheel wheel_FR("wheel_FR");
sc_start();
}
```

Simple and to the point.

Indirect Top-Level Instantiation

Example:

```
//file: main.cpp
#include "Wheel.h"
int sc_main (int argc, char* argv[] {
    Wheel* wheel_FL; // pointer to FL wheel
    Wheel* wheel_FR; // pointer to FR wheel
    wheel_FL = new Wheel("wheel_FL"); //create FL
    wheel_FR = new Wheel("wheel_FR"); //create FR
    sc_start();
    delete wheel_FL;
    delete wheel_FR;
}
```

More code, but more flexible:
looping, arrays, if then etc.
possible.

Direct Sub-Module Header-Only Instantiation

Example:

```
//file: Body.h
#include "Wheel.h"
SC_MODULE(Body) {
    Wheel wheel_FL;
    Wheel wheel_FR;
    SC_CTOR(Body)
: wheel_FL("wheel_FL"), //initialization
  wheel_FR("wheel_FR") //initialization
{
    // other initialization
}
}
```

Initializer list to be used
due to C++ rules

Indirect Sub-Module Header-Only Instantiation

Example:

```
//file: Body.h
#include "Wheel.h"
SC_MODULE(Body) {
    Wheel* wheel_FL;
    Wheel* wheel_FR;
    SC_CTOR(Body) {
        wheel_FL = new Wheel("wheel_FL");
        wheel_FR = new Wheel("wheel_FR");
        // other initialization
    }
};
```

Easier to read than
direct method.

Direct Sub-Module Instantiation

```
//file: Body.h
#include "Wheel.h"
SC_MODULE(Body) {
    Wheel wheel_FL;
    Wheel wheel_FR;
    SC_HAS_PROCESS(Body);
    Body(sc_module_name nm);
};
```

Moves the complexity of initialization to the implementation, hides it from the users of the header file.

```
//file: Body.cpp
#include "Body.h" // Constructor:
Body::Body(sc_module_name nm)
: wheel_FL("wheel_FL"),
  wheel_FR("wheel_FR"),
  sc_module(nm)
{ .. other initialization ..}
```

Indirect Sub-Module Instantiation

```
//file: Body.h  
struct Wheel;  
SC_MODULE(Body) {  
    Wheel* wheel_FL;  
    Wheel* wheel_FL;  
    SC_HAS_PROCESS(Body);  
    Body(sc_module_name nm);  
};
```

Moves the complexity of initialization to the implementation, hides it from the users of the header file.

```
//file: Body.cpp  
#include "Wheel.h" // Constructor:  
Body::Body(sc_module_name nm)  
: sc_module(nm)  
{wheel_FL=new Wheel("wheel_FL");  
  wheel_FR=new Wheel("wheel_FR");  
  .. other initialization .. }
```


Contrasting Implementation Approaches

Level	Allocation	Pros	Cons
Main	Direct	Least code	Inconsistent with other levels
Main	Indirect	Dynamically configurable	Involves pointers
Module	Direct Header only	All in one file, easier to understand	Requires sub-module headers
Module	Indirect Header only	All in one file, dynamically configurable	Involves pointers
Module	Direct with separate compilation	Hides implementation	Requires sub-module headers
Module	Indirect with separate compilation	Hides sub-module headers and implementation, dynamically configurable	

Hello World in SystemC


```
//FILE:main.cpp
#include <Hello_SystemC.h>
int sc_main(int argc, char* argv[]) {
    const sc_time t_PERIOD(8,SC_NS);
    sc_clock clk("clk",t_PERIOD);
    Hello_SystemC iHello_SystemC
        ("iHello_SystemC");
    iHello_SystemC.clk_pi(clk);
    sc_start(10);
    return 0; }
```

```
//FILE:Hello_SystemC.cpp
#include <Hello_SystemC.h>
void Hello_SystemC::main_method(void)
{std::cout << sc_time_stamp() <<
  " Hello world!" << std::endl;
}
```

```
#ifndef HELLO_SYSTEMC_H
#define HELLO_SYSTEMC_H
//FILE:Hello_SystemC.h
#include <systemc.h>
#include <iostream>
SC_MODULE(Hello_SystemC) {
    sc_in_clk clk_pi;
    void
    Hello_SystemC::main_method(void);
    SC_CTOR(Hello_SystemC) {
        SC_METHOD(main_method);
        sensitive << clk_pi.neg();
        dont_initialize();
    };
#endif
```

Source & ©: D. Black, J. Donovan,
<http://eklektically.com/Book/>; All usage
restrictions imposed by the authors apply.

SystemC language architecture



Contents

- Introduction
- Data types
- A Notion of Time
- Modules
- Concurrency
- Structure
- ➔ ■ Communication
- Channels
- Advanced Topics



Events

An event is an object represented by **sc_events**, that determines whether and when a process's execution should be triggered or resumed.

An event is used to represent a condition that may occur during the course of simulation and to control the triggering of processes accordingly.

The **sc_event** class provides basic synchronization for processes.

Events

Distinction between

- event (“subjunctive mood”) and
- actual occurrence of an event (“indicative mood”).


An event is usually associated with some change of state in a process or of a channel.

The owner of the event is responsible for reporting the change to the event object.

The act of reporting the change to the event is called **notification**.

Event

Event notification and process triggering



Triggering events: .notify

Events are created with **.notify()**.

- **Immediate notify's** move waiting processes immediately from the waiting pool to the ready pool.

Examples:

```
event_name.notify(); notify(event_name);
```

- **Delayed notification:**

```
event_name.notify(SC_ZERO_TIME);
```

```
notify(event_name, SC_ZERO_TIME);
```


Processes waiting will execute at the next δ cycle.

- **Timed notification** lets processes execute after the indicated time.

```
event_name.notify(t); notify(event_name, t);
```




Simulation engine (simplified)




Transitions between thread states

- Predicate/transition net model \approx activity chart \rightarrow queuing model -



Transitions between thread states

- Predicate/transition net model \approx activity chart \rightarrow queuing model -




@ simulation start:

- **dont_inits**: placed in τ waiting for static sensitivity event
- others: placed in ready

non-deterministic
choice between
ready threads

Transitions between thread states

- Predicate/transition net model \approx activity chart \rightarrow queuing model -




@ simulation start:

- **dont_inits**: placed in τ waiting for static sensitivity event
- others: placed in ready

ready pool emptied,
before next δ cycle
starts

Transitions between thread states

- Predicate/transition net model \approx activity chart \rightarrow queuing model -




@ simulation start:

- `dont_inits`: placed in τ waiting for static sensitivity event
- others: placed in ready

next δ cycle

Transitions between thread states

- Predicate/transition net model \approx activity chart \rightarrow queuing model -




@ simulation start:

- **dont_inits**: placed in τ waiting for static sensitivity event
- others: placed in ready

next δ cycle ...

Transitions between thread states

- Predicate/transition net model \approx activity chart \rightarrow queuing model -




@ simulation start:

- **dont_inits**: placed in τ waiting for static sensitivity event
- others: placed in ready

there can be several δ cycles

Transitions between thread states

- Predicate/transition net model \approx activity chart \rightarrow queuing model -




@ simulation start:

- **dont_inits**: placed in τ waiting for static sensitivity event
- others: placed in ready

there can be several δ cycles ...

Transitions between thread states

- Predicate/transition net model \approx activity chart \rightarrow queuing model -




@ simulation start:

- **dont_inits**: placed in τ waiting for static sensitivity event
- others: placed in ready

now the blue thread is the 1st thread to become ready; simulation time is advanced.

Transitions between thread states

- Predicate/transition net model \approx activity chart \rightarrow queuing model -



@ simulation start:

- **dont_inits**: placed in τ waiting for static sensitivity event
- others: placed in ready

and the blue thread is executed

Control flow representation

```

While there is a process in the  $\tau$  pool
  While there is a process in the “ $\delta$ ” pool
    While there is a process in the ready pool
      {take any process
      execute: evaluate signal changes;
      may send event notifications
        • immediate ( $\rightarrow$  put into ready pool),
        • delayed ( $\rightarrow$  “ $\delta$ ” pool, with 0 time)
        • timed ( $\rightarrow$  waiting pool, with time)
      until process completes (via return) or
      suspends (via calls to wait()); process to
      pool}
  
```



Update pending signal changes; (see **sc_signal**)

processes waiting in “ δ ” pool \rightarrow re

If \exists process $\in \tau$ pool: advance time

```

// macroscopic time loop
//  $\delta$  time loop
// same  $\delta$  time
  
```



Event

Events can have only one pending notification, and retain no „memory“ of past notifications.

Multiple notifications to the same event, without an intermediate trigger are resolved according to the following rule:

An earlier notification will always override one scheduled to occur later, and an immediate notification is always earlier than any δ -cycle delayed or timed notification.

sc_event_queue

Event queues allow single events to be scheduled multiple times. If events are scheduled for the same time, they will be separated by a cycle. All scheduled events can be cancelled with the **.cancel_all()** method.

Example:

```
sc_event_queue action;  
action.notify(20,SC_MS); // schedule for 20 ms from now  
action.notify(1.5,SC_NS); // schedule for 1.5 ns from now  
action.notify(SC_ZERO_TIME); // for next  $\delta$  cycle  
action.cancel_all();
```

Summary

- Modules are key design entities and can be created with **SC_MODULE**.
- Constructor **SC_CTOR** or **SC_HAS_PROCESS** required.
- There are two types of processes within modules:
 - **SC_THREAD**: started once, may contain **wait**,
 - **SC_METHOD**: run to completion, cannot call **wait**, may call **next_trigger**.
- 6 different ways of describing structural hierarchy
- Events can be used for notifications
- The simulation cycle uses an evaluation/update cycle for signal updates, corresponding to the δ -cycle of VHDL.