

Written Exercise Sheet 3

Hints: These assignments will be discussed at E23 from 10:15 AM - 11:45 AM on 05. Dez. 2017. You are not obligated to turn in the solutions.

1 Hardware in a loop

Explain the concept “hardware in a loop”. In the era of Internet of Things (IoT), for some cases, we are replacing the sensors with *human beings*. What are the potential issues when we use human beings to collect the information?

2 Internet of Things (IoT)

IoTs have become a very hot topic recently. How will you define IoT? How will IoT change the (focus of) the concept of “hardware in a loop”? If a company is very good at controlling and designing actuators, what are the challenges that the company may face if IoT become mature?

3 Aliasing

Do we lose information due to sampling? What is the problem due to *Aliasing*? Suppose that the incoming signal has a frequency 4000Hz, e.g., human voices. What is the minimum sampling rate we need to avoid aliasing?

4 Conversion

Suppose our voltage range $V_{min}..V_{max}$ is [0 V .. 4 V] and V_{ref} is 4 V. Digital values are supposed to be encoded as unsigned numbers in 4 bits. Input voltages are $V_{in} = 2.3$ V; 3.7 V and 1.8 V. Conversion is assumed to be done in cycles by successive approximation. Specify for each input voltage and for each step of the approximation cycles:

- the voltage used for comparison,
- the intermediate binary representation.

5 Pipeline analog-to-digital converter

The pipeline analog-to-digital converter is another option to digitalize analog signals.

- Describe the general functioning of a pipeline analog-to-digital converter.
- List advantages and disadvantages of a pipeline analog-to-digital converter.
- Compare the pipeline analog-to-digital converter with the well-known flash and successive approximation converters.

Hint: Browse the internet to answer this question.

6 Energy and Power

Energy and power consumption are both important in embedded systems. Give concrete reasons for minimizing power consumption. Give concrete reasons for minimizing energy consumption.

7 DVFS

Which equation describes the (dynamic) power consumption of CMOS? Let's assume that the static power consumption is 0 and the execution time is proportional to $1/f$ (not true in practice), where f is the CPU frequency. Suppose that the CPU frequency is proportional to the supply voltage. Draw the power consumption with respect to the CPU frequency. To finish the same workload by reducing the CPU frequency from 1 GHz to 0.5 GHz, how much energy can we save? If we can use $M \geq 2$ processors to finish the same workload at the same time span, draw the energy consumption with respect to M .

8 Sampling Theorem

Suppose that we sample the signals at time 0, 1, 2, 3, 4, 5, 6, 7, 8 with the following values:

t	0	1	2	3	4	5	6	7	8
values	0	1.1	1	0.3	0	-0.2	-1	-1.2	0

Explain and draw the original signal by using the $\text{sinc}()$ function.

9 Saturating arithmetic

Suppose that the numbers in the following table are given. Please compute the result of the indicated operation using wrap-around and saturating arithmetic!

a		b		op	a op b	
(un)signed	bitvector	(un)signed	bitvector		wrap-around	saturating
signed	00011 ₂	signed	00110 ₂	+	01001 ₂	01001 ₂
signed	01110 ₂	signed	01111 ₂	+	11101 ₂	01111 ₂
signed	11110 ₂	signed	11100 ₂	+	11010 ₂	11010 ₂
signed	01010 ₂	signed	01011 ₂	*	01110 ₂	01111 ₂
unsigned	10111 ₂	unsigned	10110 ₂	+	01101 ₂	11111 ₂

10 Fixed point arithmetic

Suppose that the fixed-point numbers in the following table are given. Numbers are assumed to be signed. Please compute the result of the indicated operation!

a		b		op	a op b	
(iwl, fwl)	bitvector	(iwl, fwl)	bitvector		(iwl, fwl)	bitvector
(3,2)	00110 ₂	(3,2)	00110 ₂	+	(3,2)	01100 ₂
(3,2)	00110 ₂	(3,2)	01001 ₂	+	(4,2)	001111 ₂
(3,2)	00110 ₂	(4,1)	01100 ₂	+	(4,1)	01111 ₂
(3,2)	00010 ₂	(4,1)	00010 ₂	+	(2,2)	0110 ₂
(3,2)	00110 ₂	(4,1)	00110 ₂	*	(7,3)	0000010010 ₂